

Carbon Monoxide Detector

w/Lithium Battery Tamper Resistant

- Lithium Battery Powered
- Electrochemical Sensor
- Sensor Life Monitor
- Tamper-Resistant
- ANSI/UL 2034-09 Listed
- CSA and IAS Certified
- NFPA 720 Compliant
- Five Year Warranty

PRO-TECH



0250120 Battery Powered

0250121 Plus Digital Display

Carbon Monoxide Detector

Plug-In with 9v Battery Back-Up, Digital Display

Plug-in carbon monoxide alarm with digital display and 9V battery backup meets most state and local codes for carbon monoxide alarms.

Electrochemical Carbon Monoxide Sensor - the most accurate sensor available as compared to other sensing technologies.

- Single Button Test/Silence
- Battery Backup
- Two silence features - can silence the low-battery chirp for up to eight hours or temporarily silence an unwanted nuisance alarm
- Digital Display - shows visual confirmation of CO levels in PPM
- Peak Level Recall Button - recalls the highest level of Carbon Monoxide detected
- 5-Years Limited Warrant




0250108 Plug-In, 9v Back-Up

Triangle Cast Equalizer


Rugged cast. Use 1/2" or 9/16" dia. shackle bolts.

Stock #	A	B	C	D
0157170	6"	4"	9/16"	1-3/4"



Banana Equalizer

Heavy 1/4" steel with new strong design to distribute load, preventing undue stress to axles or mobile home frame. Uses 1/2" or 9/16" dia. shackle bolts.



Stock #	A	B	C	D
0157164	5-5/8"	2-13/16"	9/16"	9/16"



U-Bolt w/Nut


1/2" dia. for mounting to 3" dia. axle tube. Self-locking nuts included.

0156915 mono-leaf spring

0156925 four-leaf spring

Bearing Cup

Shaft dia. 1-3/8"



0157182 L 68111

Bearing Cone

L 68149, high grade alloy steel. Shaft dia. 1-3/8"

0157184

LM 67048, high grade alloy steel. Shaft dia. 1-1/4"

0157188



Carbon Monoxide Detector

Samples air once every second
Calibrated at four levels for accuracy
Silencer button, re-alarms if levels persist
Unique self testing system alerts if malfunctions.



0250104
0250105



0250106

0250104 Plug-In w/Battery Back-Up
(2 - AA batteries)

0250105 Plug-In

0250106 Battery Powered
(2 - AA batteries)

Combo Alarm Smoke Detector & Carbon Monoxide Detector

Battery Powered.
The BRK First Alert
Combination Carbon
Monoxide and Smoke
Alarm protects you
from the very real
dangers of both fire
and smoke as well as
carbon monoxide.




0250103 Battery Powered
Use 2-AA Batteries

Outdoor Improvements
Anchors & Set-Up Material
Doors & Windows
Coatings & Cleaners
Appliances
Tools & Hardware
Carpet & Flooring
Electrical
Plumbing
Towing & Safety
Heating & Cooling

Shur-Set III™ Breakaway Kit

Mounts on jackpost or A-frame. Quick, easy, one-bolt installation—no cutting or drilling needed. Rust-proof polyethylene plastic case protects battery and charger from elements and corrosion. Meets or exceeds DOT specifications regarding breakaway/holding requirements.

Complete kit includes: battery case with mounting bracket; 12V sealed, rechargeable battery; and nylon breakaway switch. Battery charger sold separately.



- 0340105** Breakaway Kit; 10/Ctn.
- 0340103** Switch Only; 20/Ctn.

Lug Bolt



1/2" dia. For use with cast hubs that are drilled and tapped.

- 0154109** 1/2 - 13 threads. 2-1/4" long.
- 0153108** 1/2 - 20 threads. 1-7/8" long.

Lug Stud

Plated 1/2" dia., 2" long, 1/2-20 threads. Fits only Continental axles with formed steel hubs.



- 0157124**

Shackle Bolt & Nut



Steel, 9/16" dia. and 3" long. Hex lock nut included.

- 0157166**

Lug Nut

Plated steel, 1/2" with 20 threads per inch. Heavy hex.



- 0157130**

Universal Rim Clamp

Heavy-cast. Universal, will fit most mobile home axles, fits axles using either lug bolts or lug studs. Sometimes referred to as wedges.



- 0157125**

Dust Cap


Universal plated, will fit most axles, keeps grease in and dirt out to protect bearings.



- 0156900**

Breakaway Switch


Sets trailer brakes in case of accidental trailer breakaway. Trailer brakes are applied automatically. Reinforced nylon case. Rust and corrosion free to assure long life. Silver contact points remain corrosion free for positive contact. Nylon pull-pin can't freeze up, assuring positive activation.



- 0340103**

Battery Charger

12 volt. Fits securely in battery case with battery. Compatible with all automotive electrical systems. Automatic shutoff prevents overcharging. Designed to provide exact amperage needed to sealed, wet cell battery.



- 0340106** Battery Charger

Spring Hanger

1/4" thick heavy steel, for use w/1-3/4" wide spring.

- 0157161** 3" long, drop 2-1/4". For use with 9/16" or 1/2" dia. shackle bolt.
- 0157168** 1-3/4" long, drop 1-1/8". Use only at shackle end of single axle suspensions.
- 0157160** 13" long, drop 3-1/4". Use with 9/16" or 1/2" dia. x 3" shackle bolt.



Shackle Link

1/4" thick steel, 1-1/4" wide. Use with 1/2" or 9/16" dia. shackle bolt to connect to equalizer or to spring hanger.



- 0157162** 2-9/16" Hole Center
- 0157163** 2-1/4" Hole Center

Spindle Nut

Universal assembly comes with 1" dia. washer, 1/8" x 1-1/2" long cotter pin, and 1" dia. slotted hex nut.



- 0157172**

Grease Seal

ABS plastic, long-wearing. (Refer to old seal dimension before ordering).



- 0157174** 2-9/16" OD, 1.840" ID lip seal.
- 0157176** 3-3/8" OD, 2.245" ID lip seal