

# Vinyl Floor Covering

We now offer vinyl floor covering direct from the manufacturer by special order.



- ▲ Speedy shipping direct from Dalton, GA
- ▲ First-quality, no wax, satin-gloss standard Wearlayer
- ▲ Standard limited warranty
- ▲ 14-foot width for virtually seamless installations
- ▲ Easy to install and maintain

**Style Choices**

- Plank
- Gray Diamond
- Medallion Marble
- Taupe Ceramic
- Beige Ceramic

**0261515 14' Wide**

**Important:**

All design illustrations are reproduced as faithfully as fine color printing inks will permit. Due to the difference between printing inks and the pigments used in the manufacture of these floor coverings, we cannot guarantee exact color reproduction. Ask your salesman to show you actual sample boards.



**Plank**  
PJ014



**Gray Stone**  
PJ112



**Gray Slate**  
PJ180



**Beige**  
PJ285

- ▲ Speedy shipping direct from Dalton, GA
- ▲ First-quality, no wax, satin-gloss standard Wearlayer
- ▲ Standard limited warranty
- ▲ 14-foot width for virtually seamless installations
- ▲ Easy to install and maintain

**Style Choices**

- Plank
- Gray Stone
- Gray Slate
- Beige

Same as above, but in 15' 6" width for even wider installations.

**0261514 15' 6" Wide**

# Laminate Floor Covering 6mm

## HDF Floating Laminate



**0261528** Floating Laminate, 6mm

**0261529** T-Molding (7'10" long)

**0261530** End Cap (7'10" long)

**0261531** Reducer (7'10" long)

**0261512** Underlayment (7'10" long)

### Style Choices

Red Oak

Gunstock

Light Oak



Durable 3 mil, non-skid polyethylene film prevents damage during high traffic display periods, bad weather or while repairs are being made. Pressure-sensitive adhesive on one side, reverse rolled for easy application. Roll it across the floor, or use the handy Excaber applicator for fast, wrinkle-free application. To remove, simply peel off and discard. Non-transferable adhesive will not harm carpets.

**0265010** 23.5" x 1000' Roll

**0265011** 23.5" x 200' Roll

**0265015** Excaber Applicator

#### NOTE:

Should not be left in place for more than 45 days. It should be removed or replaced sooner if subjected to heavy foot traffic, high humidity, high temperatures or direct sunlight. Not recommended for natural fiber (wool) carpets. Do not use on marble, tile, vinyl, counter tops, etc. where it is difficult to remove. Temperatures greater than 100° F may prevent Carpet Armour from releasing properly.