


Wiring Devices

Two-Gang

Plastic. OD: 1-3/4" D, 3-1/4" H, 4-1/16" W. Ears securely molded to box. Wire clamps included; bulk packaged.



0221104

Single-Gang


Plastic. OD: 1-3/4" D, 3-3/4" H, 2-3/8" W. Ears securely molded to box.



- 0221103 W/Ears
- 0221105 W/Ears & Swing Bracket
- 0222325 Plastic Wings (Pawls)
- 0222328 Screws for Wings

Round Box

3.5" round outlet box, 2-1/8" diameter w/high clamps, ears and snap-in bracket which secures box to wall or ceiling.



0221106

Thermostat Wire


20 gauge. UL listed.

- 0220308 2 Wire, 500'
- 0220310 5 Wire, 250'
- 0220313 8 Wire, 250'



Range Cord


4', 50 amp cord w/three #6 and one #8 conductors with molded cap and terminal plugs. 12/Ctn.



0220306

Range Receptacle

4-wire, 50 amp, 125/250-volt range receptacle with "Quick-Lok" terminals. 50/Ctn.



0224201

MH 4-Wire Dryer Cord




Round rubber jacketed wire, molded-on plug. Black 4-wire 4' for mobile homes, 30 amp. 12/Ctn.

0220307

Dryer Receptacle

4-wire, 30 amp, 125/250-volt dryer receptacle with "Quick-Lok" terminals. 50/Ctn.



0224301

3-Wire Female Plug

15 amp 125V furnished with cord clamp for heavy duty use. Standard plug with parallel prong. UL listed.



0223301 100/Ctn.

3-Wire Male Plug

Solid brass plug blades are firmly embedded in body. Terminal screw clamps are designed to contain wire and prevent binding. Terminal screws backed out – ready for wiring. Terminals to positively insulate conductors. Combination

slot/Phillips head mounting and terminal screws ease installation.

15 amp, 125V, thermoplastic rubber cord. Dia. .25 - .60". UL listed.

0223201

